




REDFIELD® REVENGE® DIAL-N-SHOOT™ 3-9x42MM RIFLESCOPE



4-PLEX® RETICLE



ABOUT

Revenge Dial-N-Shoot riflescopes feature an advanced, Fully Multi-coated Lens System for the ultimate in brightness, clarity and resolution. A fast focus eyepiece provides generous field-of-view and makes reticle focus easy to achieve and maintain. Each Revenge D-N-S comes with 5 pre-engraved elevation dials that can be used to match the ballistic profiles [bullet drop] of most popular hunting calibers. For example, if you need to take a shot at 400 yards, you simply turn the D-N-S™ elevation

adjustment to 400, hold the center of the reticle on target, and squeeze the trigger. The windage adjustment features a ¼ MOA pop-up resettable dial. All Redfield Revenge riflescopes are Nitrogen filled for a lifetime of waterproof, fog proof and shockproof performance, and are covered by the Redfield Full Lifetime Warranty.

FEATURES

DIAL-N-SHOOT ELEVATION ADJUSTMENT
INCLUDES ONE 1/4 MOA DIAL AND FOUR BDC DIALS
POP-UP RESETTABLE 1/4 MOA FINGER-CLICK WINDAGE ADJUSTMENTS
SUPERIOR DURABILITY, IMAGE QUALITY, AND FIELD-OF-VIEW
4-PLEX® RETICLE

WATERPROOF, FOG PROOF, SHOCKPROOF
FAST FOCUS EYEPIECE
REDFIELD FULL LIFETIME WARRANTY

+

REDFIELD REVENGE DIAL-N-SHOOT 3-9x42MM RIFLESCOPE

SPECIFICATIONS

| | | | |
|-----------------------------------|--|----------------------------------|----------|
| RETICLE | 4-PLEX | | |
| ITEM NUMBER & FINISH | #120461 (MATTE) | | |
| LENS COATING | FULLY MULTI-COATED LENS SYSTEM | LINEAR FIELD OF VIEW (M @100M) | 11.0-38 |
| ADJUSTMENT MARKINGS | DNS ELEVATION IN YARDS, 1/4 MOA FINGER-CLICK WINDAGE ADJUSTMENTS | EXIT PUPIL (MM) | 14.2-4.9 |
| MAINTUBE DIAMETER | 1" | WEIGHT (OUNCES) | 14.8 |
| ENVIRONMENTAL PROTECTION | NITROGEN FILLED | WEIGHT (GRAMS) | 420 |
| ACTUAL MAGNIFICATION | 30-86 | LENGTH (IN) | 12.4 |
| LINEAR FIELD OF VIEW (FT @ 100YD) | 32.9-11.4 | LENGTH (CM) | 32.0 |
| | | MOUNTING SPACE (IN) | 5.6 |
| | | MOUNTING SPACE (CM) | 14.2 |
| | | OBJECTIVE APERTURE (MM) | 42.0 |
| | | EYE RELIEF (IN) | 3.5 |
| | | EYE RELIEF (MM) | 89 |
| | | ELEVATION ADJUSTMENT RANGE (MOA) | 70 |
| | | WINDAGE ADJUSTMENT RANGE (MOA) | 70 |

